

Features

- Enhancement mode transistor-Normally off power switch
- No reverse-recovery charge
- Low gate charge, low output charge
- Ultra high switching frequency
- Qualified according to JEDEC for target applications

Benefits

- Enable very high conversion efficiencies
- Supports high operating frequency
- Enables ultrahigh power density designs
- Improved safety & reliability due to cooler operation temperature


Applications

- AC-DC converters
- DC-DC converters
- Fast battery charging
- High density power conversion
- High efficiency power conversion



Product Summary

V_{DS}	700V
$R_{DS(on)}$ @6.0V typ.	150m Ω
I_D	10A



Package Marking and Ordering Information

Part #	Marking	Package	Packing	Reel Size	Tape Width	Qty
PWEG240N70G	EG240N70G	TO-252-2L	Tape&Reel	13 inches	16mm	2500pcs

Absolute Maximum Ratings

Parameter	Symbol	Value	Unit
Drain-source voltage ($T_j = -55^\circ\text{C}$ to 150°C)	V_{DSS}	700	V
Drain to source voltage transient ¹	$V_{(TR)DSS}$	800	
Drain to source voltage, pulsed ² $T_j = 25^\circ\text{C}$; total time < 10 h $T_j = 125^\circ\text{C}$; total time < 1 h	$V_{DSS,pulse}$	750	V
Continuous current, drain source	I_D	10	A
Pulsed current, drain source ³ $V_{GS} = 6\text{V}$; $T_{PULSE} = 10\ \mu\text{s}$; $TC = 25^\circ\text{C}$; $V_{GS} = 6\text{V}$; $T_{PULSE} = 10\ \mu\text{s}$; $TC = 125^\circ\text{C}$;	$I_{D,pulse}$	18 10	A
Gate source voltage, continuous ⁴ $T_j = -55^\circ\text{C}$ to 150°C	V_{GS}	-1.4~7	V
Gate source voltage, pulsed	$V_{GS,pulse}$	-20~10	V
Power dissipation	P_{tot}	73	W
Operating temperature	T_j	-55~150	$^\circ\text{C}$
Storage temperature	T_{stg}		
Maximum reflow soldering temperature	T_{sold}	260	$^\circ\text{C}$

1. V_{DS} , transient is intended for non-repetitive events, $t_{PULSE} < 200\ \mu\text{s}$.

2. V_{DS} , pulse is intended for repetitive pulse, $t_{PULSE} < 100\ \text{ns}$.

3. Limit was extracted from characterization test, not measured during production.

4. The minimum V_{GS} is clamped by ESD protection circuit, as shown in Figure 10.

Thermal Resistance

Parameter	Symbol	Limit value			Unit	Test Condition
		min.	typ.	max.		
Thermal resistance, junction – ambient	R_{thJA}	-	54	-	°C/W	-
Thermal resistance, junction - case	R_{thJC}	-	1.69	-	°C/W	-

Electrical Characteristic (at $T_j = 25^\circ\text{C}$, unless otherwise specified)

Parameter	Symbol	Value			Unit	Test Condition
		min.	typ.	max.		

Static characteristics

Gate threshold voltage	$V_{GS(th)}$	1.2 -	1.3 1.3	2.5 -	V	$I_D = 11.1\text{mA}, V_{DS} = V_{GS}$ $T_j = 25^\circ\text{C}$ $T_j = 150^\circ\text{C}$
Drain-to-source leakage current	I_{DSS}	- -	0.4 5	20 -	μA	$V_{DS} = 700\text{V}, V_{GS} = 0\text{V}$ $T_j = 25^\circ\text{C}$ $T_j = 150^\circ\text{C}$
Gate-source leakage current	I_{GSS}	-	50	-	μA	$V_{GS} = 6\text{V}, V_{DS} = 0\text{V}$
Drain-source on-state resistance	$R_{DS(on)}$	-	150	240	m Ω	$V_{GS} = 6\text{V}, I_D = 3\text{A}, T_j = 25^\circ\text{C}$
		-	288	-	m Ω	$V_{GS} = 6\text{V}, I_D = 3\text{A}, T_j = 125^\circ\text{C}$
Gate resistance	R_G	-	2.5	-	Ω	$f = 1\text{ MHz}; \text{ open drain}$

Dynamic characteristics

Input Capacitance	C_{iss}	-	80	-	pF	$V_{GS} = 0\text{V}, V_{DS} = 400\text{V},$ $f = 100\text{KHz}$
Output Capacitance	C_{oss}	-	29	-		
Reverse Transfer Capacitance	C_{rss}	-	0.1	-		
Effective output capacitance, energy related ¹	$C_{o(er)}$	-	36	-		$V_{GS} = 0\text{V}, V_{DS} = 0\text{V} \sim 400\text{V},$
Effective output capacitance, time related ²	$C_{o(tr)}$	-	52	-		
Output charge	Q_{oss}	-	21	-	nC	
Turn-on delay time	$t_{d(on)}$	-	2	-	ns	$V_{GS} = 6\text{V}, V_{DS} = 400\text{V},$ $R_{G_on(ext)} = 10\Omega, I_D = 6\text{A},$ $R_{G_off(ext)} = 2\Omega, L = 318\mu\text{H},$ See Figure 22
Rise time	t_r	-	5	-		
Turn-off delay time	$t_{d(off)}$	-	4	-		
Fall time	t_f	-	6	-		

1. $C_{o(er)}$ is the fixed capacitance that gives the same stored energy as C_{oss} while V_{DS} is rising from 0 to 400 V.

2. $C_{o(tr)}$ is the fixed capacitance that gives the same charging time as C_{oss} while V_{DS} is rising from 0 to 400 V.

Gate charge characteristics

Gate Total Charge	Q_G	-	2	-	nC	$V_{DS}=400V, I_D=3A$ $V_{GS}=0V-6V$
Gate-Source charge	Q_{GS}	-	0.2	-		
Gate-Drain charge	Q_{GD}	-	0.7	-		
Gate Plateau Voltage	V_{Plat}	-	2.5	-	V	$V_{DS}=400V, I_D=3A$

Reverse Device Characteristic

Parameter	Symbol	Value			Unit	Test Condition
		min.	typ.	max.		
Source to Drain reverse Voltage	V_{SD}	-	2.6	-	V	$V_{GS}=0V, I_{SD}=3A$
Pulsed current, reverse	$I_{S,pulse}$	-	-	18	A	$V_{GS}=6V, t_{PULSE}=10\mu s$
Reverse recovery charge	Q_{rr}	-	0	-	nC	$I_S=3A, V_{DS}=400V$
Reverse recovery time	t_{RR}	-	0	-	ns	
Peak reverse recovery current	I_{rrm}	-	0	-	A	

Typical Performance Characteristics

Fig 1: Typ. Output Characteristics




Fig 2: Typ. Output Characteristics




Fig 3:
Typ. Drain-source on-state resistance




Fig 4:
Typ. Drain-source on-state resistance




Fig 5:
Typ. channel reverse characteristics




Fig 6:
Typ. channel reverse characteristics




Fig 7:
Typ. channel reverse characteristics




Fig 8:
Typ. channel reverse characteristics




Fig 9: Typ. Transfer Characteristics




Fig 10: Typ. Gate-to-Source leakage




Fig 11: Drain-source leakage characteristics




Fig 12: $V_{GS(th)}$ vs. Temperature




Fig 13: $R_{DS(on)}$ vs. Temperature




Fig 14: Power Dissipation




Fig 15:
Max. Transient Thermal Impedance




Fig 16: Safe Operating Area




Fig 17: Safe Operating Area




Fig 18: Gate Charge Characteristics




Fig 19: Capacitance Characteristics




Fig 20: Typ. output charge






Fig 21: Typ. C_{OSS} stored Energy




Test Circuit & Waveform

Fig 22: Typ. Switching time with inductive load




$V_{DS}=400V$, $I_D=6A$, $L=318\mu H$,
 $V_{GS}=6V$, $R_{on}=10\Omega$, $R_{off}=2\Omega$

Fig 23: Typ. Switching times waveform



Package Outline: TO-252-2L



SYMBOL	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	2.15	2.45	0.085	0.096
A1	0.05	0.20	0.002	0.008
A2	0.91	1.22	0.036	0.048
B	0.66	0.86	0.026	0.034
B1	0.93	1.23	0.037	0.048
C	0.40	0.60	0.016	0.024
C1	0.40	0.60	0.016	0.024
D	5.95	6.25	0.234	0.246
D1	4.80		0.189	
D2	3.80		0.150	
E	6.45	6.75	0.254	0.266
E1	5.12	5.52	0.202	0.217
L	1.65		0.065	
L1	1.58	1.98	0.062	0.078
L2	0.60	1.00	0.024	0.039
L3	0.70	1.00	0.028	0.039
L4	0.00	0.20	0.000	0.008
L5	2.80	3.40	0.110	0.134
H	9.80	10.40	0.386	0.409
θ	0.00	8.00	0.000	0.315
e	4.57		0.180	

Disclaimer

Any and all semiconductor products have certain probability to fail or malfunction, which may result in personal injury, death or property damage. Customer are solely responsible for providing adequate safe measures when design their systems.

Unless otherwise specified in the datasheet, the product is designed and qualified as a standard commercial product and is not intended for use in applications that require extraordinary levels of quality and reliability, such as automotive, aviation/aerospace and life-support devices or systems.

Buyer is responsible for its products and applications using PingWei products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by PingWei.

"Typical" parameters which may be provided in PingWei data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE